



Introduction



Our latest Midilift combines design versatility and intuitive use with ease of installation and reliable performance – with more finish choices to customise your lift to suit your building and more user-friendly features for the end user.

Midilift can be installed in new and existing buildings, complementing and blending into any environment, either internally or externally. Predominantly used as wheelchair or disabled lifts, these lifts require no pit, are installed in their own structure and can travel up to 7 metres. The half height gate option, for up to 3 metres of travel, is ideal for enabling access to mezzanine floors or where there are headroom restrictions.

Our platform lifts help building designers and owners to meet the requirements of Part M and BS 8300, as well as helping to meet obligations under EN81-41 and the Equality Act (formerly the DDA), whilst taking up the minimal amount of building space possible.

A UK manufacturer, Stannah have proudly provided more than 5,000 Midilift platform lifts. These lifts are installed throughout the UK, across all market sectors, including education, retail, offices, public buildings and private residences. Our proven hydraulic drive and energy-efficient lighting coupled with our nationwide service ensures our lifts run smoothly and efficiently for years, adding value to any building.





Products

Products

There are two products in the Midilift range, both of which are suitable for indoor and outdoor use.

Midilift SL

The Midilift SL platform lift travels up to 7 metres providing a solution for higher travel and an increased number of stops. There is a wide range of design options for the structure and platform to ensure the lift matches your building requirements.


Midilift GL

The Midlift GL platform lift is a low-cost option for mezzanine floors. This lift travels up to 3 metres with a half height gate at the top. It can also be an ideal solution if headroom is restricted on the second floor.









Key benefits

Key benefits

console

- Up to 7m travel with three platform sizes available to suit buildings of different shapes and sizes
- · Compact shaft with a choice of entrance configurations
- · Minimal builders work required and quick installation time
- · Structure-supported enclosure no lifting beam required
- · Flexibility on drive control unit location
- Low pit requirements with ramp where a 70mm recess is not possible
- Low running and maintenance costs due to the single phase power consumption
- Choice of finishes or branding to complement any building design and to make your lift unique
- · Helps building owners to conform with Part M and the Equality Act
- · Finish and specification for outdoor and indoor use

The external option for the Midilift means you have a lift built for outdoors, with a specification to withstand extreme temperatures and a 5-year anti-corrosion warranty.

BREEAM

A Stannah Midilift falls under the Machinery Directive, which means it travels at no faster than 0.15m/s. By choosing this lift as opposed to a passenger lift, the BREEAM criteria does not apply and your overall BREEAM score is reduced as a result.

Installation & Warranty

Installation typically takes 1-4 days, depending on site conditions and lift travel.

All our lifts are supplied with a 12-month warranty with four service visits as standard and we offer a range of service options tailored to suit your specific requirements.

Stannah also offer cabin platform lifts – the Midilift Plus range

offering the feel of a passenger lift but with all the access benefits of a platform lift – ask for further details.

operation



buttons

option

contrast design

Features and options at a glance

Standard features:

Carriage:

Moving platform and console within lift structure

Large illuminated constant pressure call buttons – 50mm square

Audible and visual notification of floor level and travel direction

Voice annunciation with arrival chime

Alarm button

Emergency stop switch

Red digital display units with direction arrow and overload indicator

Battery backed up LED lighting

Handrail in satin stainless steel

Mechanical safety edges around platform

Landing features:

Complete lift isolation keyswitch (supplied on lower landing only)

Landing controls:

One-touch landing controls mounted on lift door frame

Other features:

Automatic emergency lowering feature

Two-way intercom communication system for emergency calls

Emergency lighting and alarm with back-up battery

Structure:

Structure supported enclosure with powder coated steel solid infill panels

LED ceiling spot lights with timer (SL only)

Doors:

Panoramic glass door fitted with door closer 800/900mm clear opening at each entrance

The Midilift helps to meet the requirements of:

- The Equality Act
- Part M of the Building Regulations (England and Wales) and Section 4.2 of the Technical Handbook (Scotland), both of which cover the requirements that many new buildings must meet to ensure ease of access and use
- BS8300:2009 Code of Practice covering the design of buildings and their approaches to meet the needs of disabled people

All of our Midilifts are CE marked and comply with the latest Machinery Directive 2006/42/EC.

Options available:

Carriage:

Joystick - 2 floor lift only

Landing features:

Key operated locking control at each landing to restrict lift access

Red digital display units with fixed direction arrow

Landing controls:

Flush wall mounted landing controls

Pedestal mounted landing controls

Other features:

Battery backup in both directions

Klaxon alarm fitted to structure

Emergency telephone (phone line supplied separately)

Memcom auto-dialler/auto-dialler with inductive loop

Fire alarm shutdown (to lowest floor only)

Welsh signage and instructions

Outdoor control cabinet

Structure:

Glass infill panels (clear or tinted)

Fixed ramp at the lower level

Special fixing brackets/hoops (if required)

Pre-drilled full enclosure/landings/sides (fire cladding)

Reduced headroom †

Door options:

30/60 min fire rated door – primed or wood finish (see finishes page)

Doors by others to match overall building style

Half height gate - GL

Automatic door opener/closer

Concealed door closer

External:

External specification built to cope with a range of weather

E-coat primer with an architectural powder coat

Door canopy


Roof fan for heat extraction (optional)

Oil heater as standard for cold weather


IP54 rated buttons 50mm square

† There are instances in which we can reduce the headroom – please contact us to discuss further.

Technical data



Midilift GL with half height upper gate



Midilift SL with roof and door canopy (external option shown)

Dimensions					
Platform size (w x d)	Footprint size (w x d)	Pit depth	Headroom		
950 x 1250	1210 x 1410◊	70*	Variable –		
950 x 1400#	1210 x 1530◊	70*	please see notes [†]		
1100 x 1400#‡	1330 x 1530◊	70*			

Technical specifications					
	Midilift GL ½ height gate	Midilift SL Full height door			
Standard load	400kg				
Maximum travel	3m	7m			
Speed of travel	Up to 0.15m/s				
Drive system	Hydraulic (includes separate pump)				
Platform control system	Constant pressure				
Power supply	240v single phase				

Notes

All dimensions are in mm

- * A ramp can be used where this pit depth is not possible.
- † Headroom is dependent upon the travel please contact us for more information.
- # Part M (England and Wales) compliant (950 \times 1400 for unattended wheelchair use and 1100 \times 1400 for attaended use).
- ‡ Section 4.2 (Scotland) compliant.
- \Diamond For aperture, allow +30mm on each dimension over and above the footprint.



055

NBS Specifications, CAD blocks and data sheets giving further technical information are all available from our web site

www.stannahlifts.co.uk/downloads


Finishes

	Standard	Options	
Structure, door frame, carriage and platform	White	Light Grey	Dark Grey
Mid panel	Dark Grey	Stainless Steel	Light Grey
Floor	Grey Safety Floor Aluminium chequer plate floor	Vinyl stud Light Grey Slate effect	Vinyl stud Dark Grey Oak effect
	(standard on external model)	PVC laminate Flooring by others	
Doors	White	Light Grey	Dark Grey
Fire doors (optional)	Beech White Oak	Red Oak	Ash
Infills	White	Glass	Tinted Glass

Bespoke Options

Our bespoke solutions offer you a wide range of RAL colours on all of the above components. Choose from a wide range of alternative finishes to ensure your lift meets your specifications. Colours, glass, flooring and more can be selected from a wide range of materials.





Samples can be provided on request - please call 01264 339090.

The colours and designs reproduced in this document have been matched as closely as printing will allow. It is recommended you obtain samples prior to specification. We are continually developing and improving our range of products and finishes and we therefore reserve the right to alter or amend the specification without prior notice.

Please note: costs may vary and are dependent on the choice of finishes selected.

Key to colours: White – BS22B15 Light Grey – RAL 7035 Dark Grey – RAL 7016 Stannah knows how to help people get on with their lives. Whether it is a passenger lift at the station, a dumbwaiter at the coffee shop, an escalator in the shopping centre, or a stairlift at home – we are there quietly helping life happen.

With over 140 years of experience and expertise in the lift industry, we offer customers right across the UK a complete range of lifting solutions to move people and goods efficiently, reliably and safely. We are proud of our reputation for outstanding customer service, delivered from our network of branches.

Whatever your lifting requirements, Stannah can provide a solution.



Anton Mill, Andover, Hampshire SP10 2NX

Telephone: 01264 339090

Meet the family



Stairlifts



Homelifts











Passenger lifts



goods lifts



lifts



Escalators and moving walkways



Loading systems



Lift refurbishments, service and repair

